




Lightweight AAC blocks that reduce loads and enable a sustainable tomorrow



ABOUT US

Prism Johnson Limited is one of India's largest integrated building materials companies, offering a wide range of products—from cement and ready-mixed concrete to tiles and bath products.

Prism Johnson strives to provide high-quality and innovative building material products and services while addressing society's needs in a sustainable manner. The company believes that a superior customer experience forms the foundation for long-lasting partnerships. To this end, it continuously customises products and solutions to meet customer requirements and ensure higher satisfaction.







OUR BRANDS













OUR PRODUCTS



CEMENT





TILES



SANITARYWARE & BATH FITTINGS



READY-MIXED CONCRETE



CONSTRUCTION CHEMICALS



PLASTER





PrismGreenWall by Prism Johnson Limited is a sustainable and innovative solution for modern construction, engineered from eco-friendly materials to minimize environmental impact while delivering superior performance. These lightweight autoclaved aerated concrete (AAC) blocks are designed to reduce structural loads, ensuring cost-efficiency, durability, and long-term reliability.

PrismGreenWall offers advanced features including superior thermal and sound insulation, exceptional fire resistance, and low water absorption, making it versatile for various construction applications. With a density just one-third that of conventional clay bricks, it streamlines construction processes, minimizes material wastage, and boosts overall efficiency. PrismGreenWall is the ideal solution for environmentally conscious projects, blending sustainability with outstanding performance.



KEY FEATURES



KEY ADVANTAGES







insulation





structural costs



TECHNICAL SPECIFICATIONS

Density (Oven Dry)	550 - 650 kg/m ³
Compressive Strength	4 N/mm ²
Modulus of Elasticity	2040 N/mm ²
Drying Shrinkage	0.04%
Fire Resistance	4 Hrs. (for 150 mm wall)
Thermal Conductivity (k value)	0.16 W/(m.k)
Water Absorption (At equilibrium)	8%
Sound Transmission Class Rating	43db (for 100 mm wall)
Coefficient of Thermal Expansion	8.1×10 ⁻⁶ K ⁻¹

PrismGreenWall VS Others



PROPERTIES	RED BRICK	CONCRETE BLOCK	PrismGreenWall
Thermal Conductance	0.81 W/m ² .K	2 W/m ² .K	0.16 W/m ² .K
Dry Mass Density	1800-2000 kg/m ³	2500 kg/m ³	550-650 kg/m ³
Material Constituents	Top Soil	Cement + Water + Sand & Gravel	Fly Ash + Gypsum + Lime + Cement + Aluminum Powder
Power Efficiency	Low	Average	High (30% less electricity consumption on HVAC)
Water Permeation	High	Average	Low
Pest & Termite	High	None	None
Shock Resistance	Low	Low	Highest in the category
Fire Durability (6 wall)	2 hours	3 hours	4 hours
Breakage Residue	High 10% to 12%	Minimal (1%-3%)	Minimal (1%-3%)



ADDRESS

Prism Johnson Limited, RMC (India) Division, 7th Floor, Windsor, C.S.T Road, Near Vidyanagari Mumbai University, Kalina, Mumbai - 400098, India

PRISM JOHNSON LIMITED

SCAN ME FOR MORE!



Contact Us





+91 9769801903

